

# Storage conditions



**POLYURETHANE  
CONSUMABLE PARTS:  
ANVIL COVERS, WHEELS  
AND OTHER SPARE PARTS**



**CONSUMIBLES  
POLIURETANO:  
CUBIERTAS, RUEDAS Y  
OTROS REPUESTOS**



**CONSOMMABLES  
EN POLYURETHANE:  
CONTREPARTIES, ROUES ET  
AUTRES COMPOSANTS**



**POLYURETHAN-ERSATZTEILE:  
GEGENSTANZBELÄGE,  
NO-CRUSH-RÄDER,  
ABROLLER UND SONSTIGE  
FERTIGUNGSTEILE**



Total protection of light and UV rays (to store in closed packaging and protected from light)

Protección total de la luz y rayos UV (mantener embalaje cerrado y protegido de la luz)

Ne pas exposer à la lumière et aux rayons UV (maintenir l'emballage fermé et protégé de la lumière)

Teile gut geschützt vor Licht und UV-lagern (in verschlossener Verpackung aufbewahren)



Storage temperature:  
Between -5°C and 35°C /  
25°F and 95°F

Temperatura almacenamiento:  
Entre -5°C y 35°C /  
25°F y 95°F

Température de stockage:  
Entre -5°C et 35°C /  
25°F et 95°F

Lagerungstemperatur:  
zwischen -5°C und 35°C /  
25°F und 95°F



Relative humidity: ≤ 50%

Humedad relativa: ≤ 50%

Humidité relative: ≤ 50%

Relativer Feuchtigkeitsgehalt: ≤ 50%



Maximum storage time: 3 years

Tiempo máximo almacenamiento:  
3 años

Durée maximum de stockage:  
3 ans

Maximale Lagerzeit: 3 Jahre



**Policart Srl**  
Quality Management System  
UNI EN ISO 9001:2015  
Certified by Certiquality



Follow us on [@Policart-srl](#)